



## Coated webbing slings 2 - 4 t

### Product information



Double layered Duplex lifting slings, which are covered with special plastic. Extreme cut and abrasion resistance. These slings can be used to lift sharp-edged items without special corner protectors. Folded reinforced eyes as standard. Also available with one-sided and partial plastic coating.

[... Read more](#)

**Features:** RFID-ready

**Material:** 100% polyester

**Marking:** According to standard, CE-marked

**Temperature range:** -40°C - +100 °C

**Standard:** EN 1492-1

**Note:** Color coded

**Warning:** Standard dimensional tolerance is 3 %. Lengths can vary within the tolerance range! Also available with higher WLL.

**Safety factor:** 7:1



## Coated webbing slings 2 - 4 t

### Technical data

Part code	WLL ton	EWL m	Choke Hitch ton	Basket Hitch 0° ton	Basket Hitch 0-45° ton	Basket Hitch 45°-60° ton	Webbing width mm	Colour
SNVS202	2	2	1.6	4	2.8	2	80	Green
SNVS203	2	3	1.6	4	2.8	2	80	Green
SNVS204	2	4	1.6	4	2.8	2	80	Green
SNVS205	2	5	1.6	4	2.8	2	80	Green
SNVS206	2	6	1.6	4	2.8	2	80	Green
SNVS208	2	8	1.6	4	2.8	2	80	Green
SNVS210	2	10	1.6	4	2.8	2	80	Green
SNVS212	2	12	1.6	4	2.8	2	80	Green
SNVS214	2	14	1.6	4	2.8	2	80	Green
SNVS302	3	2	2.4	6	4.2	3	100	Yellow
SNVS303	3	3	2.4	6	4.2	3	100	Yellow
SNVS304	3	4	2.4	6	4.2	3	100	Yellow
SNVS305	3	5	2.4	6	4.2	3	100	Yellow
SNVS306	3	6	2.4	6	4.2	3	100	Yellow
SNVS308	3	8	2.4	6	4.2	3	100	Yellow
SNVS310	3	10	2.4	6	4.2	3	100	Yellow
SNVS312	3	12	2.4	6	4.2	3	100	Yellow
SNVS314	3	14	2.4	6	4.2	3	100	Yellow
SNVS402	4	2	3.2	8	5.6	4	130	Grey
SNVS403	4	3	3.2	8	5.6	4	130	Grey
SNVS404	4	4	3.2	8	5.6	4	130	Grey
SNVS405	4	5	3.2	8	5.6	4	130	Grey
SNVS406	4	6	3.2	8	5.6	4	130	Grey
SNVS408	4	8	3.2	8	5.6	4	130	Grey
SNVS410	4	10	3.2	8	5.6	4	130	Grey
SNVS412	4	12	3.2	8	5.6	4	130	Grey
SNVS414	4	14	3.2	8	5.6	4	130	Grey