

Webbing slings 0,5 - 35 t

Product information

Double layer Duplex webbing slings 0,5 - 35 t. Folded reinforced eyes as standard and also available with flat eye.

Note! Standard dimensional tolerance is $\pm 3\%$. Lengths can vary within the tolerance range!

Thanks to our own production unit, we can also make quick deliveries of special types and lengths as well as lifting slings with higher WLL UP TO 35t.

Features: RFID-ready

Material: 100% polyester

Marking: According to standard, CE-marked

Temperature range: -40°C - +100 °C

Standard: EN 1492-1

Note: Color coded

Safety factor: 7:1

Part code

WLL ton

SNV05XX

0.5

SNV0501

0.5

SNV0502

0.5

SNV0503

0.5

SNV0504

0.5

SNV0505	0.5
SNV0506	0.5
SNV0508	0.5
SNV0510	0.5
SNV1XX	1
SNV101	1
SNV102	1
SNV103	1
SNV104	1
SNV105	1
SNV106	1
SNV108	1
SNV110	1
SNV2XX	2
SNV201	2
SNV202	2
SNV203	2
SNV204	2
SNV205	2
SNV206	2
SNV208	2
SNV210	2
SNV3XX	3

SNV301	3
SNV302	3
SNV303	3
SNV304	3
SNV305	3
SNV306	3
SNV308	3
SNV310	3
SNV4XX	4
SNV401	4
SNV402	4
SNV403	4
SNV404	4
SNV405	4
SNV406	4
SNV408	4
SNV410	4
SNV5XX	5
SNV502	5
SNV503	5
SNV504	5
SNV505	5
SNV506	5

SNV508	5
SNV510	5
SNV6XX	6
SNV602	6
SNV603	6
SNV604	6
SNV605	6
SNV606	6
SNV608	6
SNV610	6
SNV8XX	8
SNV802	8
SNV803	8
SNV804	8
SNV805	8
SNV806	8
SNV808	8
SNV810	8
SNV820	8
SNV10XX	10
SNV1002	10
SNV1003	10
SNV1004	10

SNV1005	10
SNV1006	10
SNV1008	10
SNV1010	10
SNV1020	10
SNV12XX	12
SNV1204	12
SNV1205	12
SNV1206	12
SNV1208	12
SNV1210	12
SNV1220	12