



Chain sling 2-legs with safety hooks, grade 80

Product information

2-legs chain sling assembly equipped with safety hooks. Alternative ends are also available, e.g. foundry hooks, shackles etc. Slings are equipped with a load plate.

The L-dimension is measured from the inside of the top of the master ring to the inside of the bottom of the hooks.

Material: Steel Marking: According to standard, CE-marked Temperature range: -40 - (+)200°C / 400°C = WLL 75% Finish: Painted, black / yellow Standard: EN 818-4 Warning: Not to be heat-treated

Safety factor: 4:1 Grade: 8

| Part code | Chain diameter mm | WLL 0-45° t | WLL 45-60° t |
|-----------|----------------------|----------------|-----------------|
| NKV06201 | 6 | 1.6 | 1.12 |
| NKV07201 | 7 | 2.12 | 1.5 |
| NKV08201 | 8 | 2.8 | 2 |
| NKV10201 | 10 | 4.25 | 3.15 |
| NKV13201 | 13 | 7.5 | 5.3 |
| NKV16201 | 16 | 11.2 | 8 |
| NKV20201 | 20 | 17 | 12.5 |
| NKV22201 | 22 | 21.2 | 15 |
| NKV26201 | 26 | 30 | 21.2 |
| NKV32201 | 32 | 45 | 31.5 |

Blueprint

