



## Clevis self-locking hook, grade 100

### Product information

The chain is attached to the hook with clevis without a connecting link. The hook locks automatically when lifting starts.

**Material:** Steel

**Marking:** CE-marked

**Temperature range:** -40 - (+)200°C / 400°C = WLL 75%

**Finish:** Painted, blue

**Warning:** Not to be heat-treated

**Safety factor:** 4:1

**Grade:** 100

Part code	WLL ton	For chain Ø mm	P mm	M mm	T mm	H,	K,	Weight kg
VAKAH106	1.4	6	28	8	15	19	95	0.5
VAKAH1078	2.5	8	35	9	20	24	121	0.9
VAKAH1010	4	10	45	12	26	28	146	1.6
VAKAH1013	6.7	13	53	15	32	40	182	2.9
VAKAH1016	10	16	62	18	38	51	218	5.8
VAKAH1020	16	20	76	25	45	55	239	8.6
VAKAH1022	19	22	80	25	52	67	280	12.1

## Technical data

### SPARE PARTS

Spare part (product code)	Description	Suitable for ABT hook (product code)
VAKVO6S	Spare part set 6 mm   Incl. trigger, spring, pin	VAKAH106
VAKVO78S	Spare part set 7/8 mm   Incl. trigger, spring, pin	VAKAH1078
VAKVO10S	Spare part set 10 mm   Incl. trigger, spring, pin	VAKAH1010
VAKVO13S	Spare part set 13 mm   Incl. trigger, spring, pin	VAKAH1013L
VAKVO16S	Spare part set 16 mm   Incl. trigger, spring, pin	VAKAH1016
VAKVO20S	Spare part set 20 mm   Incl. trigger, spring, pin	VAKAH1020

**Warning:** If you notice that the design of the spare part trigger differs from the original, please contact the supplier - do not try to force it into place, as this may compromise the safe operation of the hook

# Blueprint

