Master link assemblies 3-4-l, grade 80

Product information

Masterlink for 3- and 4-leg chain sling assemblies.

... *Read more*



Material: Steel
Marking: According to standard, CE-marked
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, yellow
Standard: EN 1677-4
Warning: Not to be heat-treated


Safety factor: 4:1
Grade: 8

© October 2026 - All Rights Reserved

Forankra
Secures everything in transit™

Master link assemblies 3-4-I, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain, 3-4-leg mm	L mm	B mm	D mm	B1 mm	D1 mm	L1 mm	Weight kg
NRLI6	2.36	189	6	135	75	18	25	14	54	1.2
NRLI78	4.25	230	7/8	160	90	22	34	16	70	2.2
NRLI10	6.7	265	10	180	100	26	40	18	85	3.4
NRLI13	11.2	315	13	200	110	32	50	22	115	6
NRLI16	17	400	16	260	140	36	65	26	140	10
NRLI20	26.5	500	20	350	190	51	70	32	150	23.3
NRLI22	32	520	22	350	190	51	75	36	170	25.9
NRLI26	45	570	26	400	200	57	80	40	170	35.2
NRLI32	67	817	32	460	250	72	190	49	357	67.6

© October 2026 - All Rights Reserved