Master link assemblies 3-4-l, grade 100

Product information



Masterlink for 3- and 4-leg chain sling assemblies.

The chain is attached with grade 100 connecting link.

... *Read more*

Material: Steel
Marking: CE-marked
Temperature range: -40 - (+)200°C / 400°C = WLL 75%
Finish: Painted, blue
Warning: Not to be heat-treated


Safety factor: 4:1
Grade: 10

© October 2026 - All Rights Reserved

Forankra
Secures everything in transit™

Master link assemblies 3-4-I, grade 100

Blueprint



Technical data

Part code	WLL ton	For chain, 3-4-leg mm	WLL 45- 60° ton	D mm	B mm	L mm	L1 mm	D1 mm	B1 mm	Weight kg
NRLIA6	3	6	2.25	19	75	135	84	13	25	1.1
NRLIA8	5.3	8	3.75	23	90	160	70	16,5	35	2.2
NRLIA10	8	10	6	27	100	180	85	19	40	3.4
NRLIA13	14	13	10	33	110	200	115	23	50	6.1
NRLIA16	21.2	16	15	36	140	260	140	27	65	9.9
NRLIA20	33.6	20	24	50	190	350	150	33	70	26.5
NRLIA22	40	22	30	50	190	350	180	36	100	32.8

© October 2026 - All Rights Reserved