

Latch hook with ball bearing swivel, grade 80

Product information



Hook is equipped with spring loaded safety latch. Due to the swivel the hook is easy to align into the wanted direction.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-2


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Latch hook with ball bearing swivel, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain Ø mm	A mm	B mm	E mm	M mm	L1 mm	L mm	N mm	C mm	H mm	Weight kg
SALKL6KL	1.12	-	6	33	33	24	69	138	168	16	11	19	0.65
SALKL78KL	2	170	8	45	36	28	88	170	208	20	13	23	0.95
SALKL10KL	3.15	207	10	53	42	31	105	207	254	23	15	29	1.71
SALKL13KL	5.3	248	13	64	50	40	135	248	305	32	17	38	3.13
SALKL16KL	8	295	16	68	61	45	161	295	367	37	21	45	5.44
SALKL20KL	12.5	356	20	90	74	56	194	356	434	49	25	50	9.5