

Master link oversized, grade 80

Product information



Extra large masterlink for chain sling assemblies.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40 - (+)200°C / 400°C = WLL 75%

Finish: Painted, yellow

Standard: EN 1677-4


Warning: Not to be heat-treated

Safety factor: 4:1

Grade: 8

Master link oversized, grade 80

Blueprint



Technical data

Part code	WLL ton	EWL mm	For chain, 1-leg mm	For chain, 2-leg mm	A mm	B mm	D mm	Weight kg
NOR16B7	3.2	190	10	7/8	190	100	16	0.86
NORY025	6.4	300	13	10	300	210	25	5.53
NOR22B7	7	210	13	10	210	110	22	1.83
NORY032	11	300	16	13	300	210	32	5.94
NOR28B7	11.5	270	16	13/16	270	140	28	3.8
NOR32B6	17	270	22	20	270	140	32	5.05
NOR38B7	19	400	22	20	420	220	38	10.78
NOR45B7	27	470	26	22	470	250	45	17.06
NOR38B6	28	420	26	22	270	140	38	7.29
NOR50B6	45	380	36	32	380	200	50	17.65
NOR60B6	65	430	36	32	430	220	60	28.85