

Push trolley

Product information



Push trolley for IPE and T beams. The wheels are equipped with duration lubricated ball bearings. The hoist or lifter can be attached directly to the trolley eye with a hook or a shackle.

... [Read more](#)

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -10°C - (+)50°C


Finish: Painted, yellow

Standard: EN 13157

Safety factor: 4:1

Push trolley

Blueprint



Technical data

Part code	WLL ton	Beam width mm	Minimum radius mm	B mm	D mm	E mm	F mm	G mm	H mm	J mm	K mm	L mm	M mm	Weight kg
SIVA05H	0.5	55-220	500	285	3	40	12.5	25	80	198	158	55	28	5
SIVA05HL	0.5	55-305	500	385	3	40	12.5	25	80	198	158	55	28	5.4
SIVA10H	1	58-220	700	300	3	31	17	29	96	238	183	68	37	8.8
SIVA10HL	1	58-305	700	238	3	31	17	29	96	-	183	68	37	9.3
SIVA20H	2	66-220	900	300	3	31	20	36	110	277	208	80	48	14
SIVA20HL	2	66-305	900	405	3	31	20	36	110	277	208	80	48	14.8
SIVA30H	3	74-220	1,200	328	3	31	26	46	132	324	249	100	56	23
SIVA30HL	3	74-305	1,200	429	~3	31	26	46	132	324	249	100	56	24.1
SIVA50H	5	90-220	1,000	354	5	40	28	52	155	373	296.5	120	65	40
SIVA50HL	5	90-305	1,000	435	~5	40	28	52	155	373	296.5	120	65	41.1

AXEL OF THE TROLLEY

Product code	Thread	Thread pitch mm
SIVA05H	M24	1,5
SIVA10H	M30	1,5
SIVA20H	M36	1,5
SIVA30H	M42	2
SIVA50H	M48	2

Note! One end is left-hand thread and the other end is right hand thread

Push trolley
