Weld-on lifting point, grade 80

Product information

Weld-on lifting point for all lifting directions. Equipped with a spring that holds the eye in desired position.

... *Read more*



Material: Steel
Marking: According to standard, CE-marked
Temperature range: -40°C - (+)200°C
Finish: Painted, yellow
Standard: EN 1677-1


Safety factor: 4:1
Grade: 8

© October 2026 - All Rights Reserved

Forankra
Secures everything in transit™

Weld-on lifting point, grade 80

Blueprint



Technical data

Part code	WLL ton	A mm	B mm	D mm	M mm	Weight kg
NS8HI1	1.12	41	78.5	13	37	0.4
NS8HI2	2	42	88	14	40	0.47
NS8HI3	3.15	45	94	17	42.5	0.69
NS8HI5	5.3	55	118	22	50	1.46
NS8HI8	8	70	141	26.5	66.5	2.5
NS8HI15	15	97	188	34	90	5.79
NS8HI20	20	149	240	46	125	15.37

WORKING LOAD LIMITS

Product	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)	WLL (t)
					0 - 45°	45-60°	0 - 45°	45-60°
NS8HI1	1,12	1,12	2,24	2,24	1,57	1,12	2,35	1,68
NS8HI2	2	2	4	4	2,8	2	4,2	3
NS8HI3	3,15	3,15	6,3	6,3	4,41	3,15	6,62	4,73
NS8HI5	5,3	5,3	10,6	10,6	7,42	5,3	11,13	7,95
NS8HI8	8	8	16	16	11,2	8	16,8	12
NS8HI15	15	15	30	30	21	15	31,5	22,5

© October 2026 - All Rights Reserved