Forankra
Secures everything in transit™

# Stainless steel lifting eye nut DIN 582

**Product information**

Stainless steel lifting eye for vertical lifting.

... *Read more*




**Material:** AISI 316
**Marking:** According to standard, CE-marked
**Temperature range:** -40°C - (+)200°C
**Finish:** Polished
**Standard:** DIN 582
**Note:** Only for vertical lifting
**Warning:** Not to be heat-treated


**Safety factor:** 4:1

© October 2026 - All Rights Reserved

Forankra
Secures everything in transit™

# Stainless steel lifting eye nut DIN 582

## Blueprint




## Technical data

| Part code | WLL ton | Thread mm | b mm | c mm | d mm | e mm | f mm | Weight kg |
|---|---|---|---|---|---|---|---|---|
| NSMH06L | 0.08 | M6 | 20 | 36 | 20 | 8.5 | 36 | 0.05 |
| NSMH08L | 0.14 | M8 | 20 | 36 | 20 | 8.5 | 36 | 0.05 |
| NSMH10L | 0.23 | M10 | 25 | 45 | 25 | 10 | 45 | 0.09 |
| NSMH12L | 0.34 | M12 | 30 | 54 | 30 | 11 | 53 | 0.16 |
| NSMH16L | 0.7 | M16 | 35 | 63 | 35 | 13 | 62 | 0.24 |
| NSMH20L | 1.2 | M20 | 39 | 71 | 39 | 14 | 70 | 0.36 |

## WORKING LOAD LIMITS

| Thread | WLL (t) | WLL (t) | WLL (t) | WLL (t) | WLL (t) | WLL (t) | WLL (t) | WLL (t) |
|---|---|---|---|---|---|---|---|---|
| | | | | | 0 - 45° | 45-60° | 0 - 45° | 45-60° |
| M6 | 0,08 | | 0,16 | | - | | - | |
| M8 | 0,14 | | 0,28 | | 0,1 | | 0,14 | |
| M10 | 0,23 | | 0,46 | | | | | |

© October 2026 - All Rights Reserved