



Chain Sling G80 1-leg with Foundry Hook and Grab Hook

Product information

High quality 1-leg chain sling equipped with foundry hook with shortening hook. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

Material: Steel

Marking: According to standard, CE-marked

Temperature range: -40°C up to +200°C / 400°C = WLL 75%

Finish: Painted, black / yellow

Standard: EN 818-4

Safety factor: 4:1

Grade: 8

Part code	Chain diameter mm	WLL ton	EWL m	Weight kg
42070923W	6	1.12	0.5	9.21
42070926W	6	1.12	1.5	10.01
42070937W	6	1.12	3	11.21
42070383W	6	1.12	1	11.31
42070949W	6	1.12	6	13.61
42070932W	6	1.12	2	15.51
42070930W	6	1.12	2.5	15.91
42070934W	6	1.12	3.5	16.71

42070941W	6	1.12	4	17.11
42070945W	6	1.12	5	17.91
42070953W	8	2	0.5	11.636
42070960W	8	2	1	12.311
42070956W	8	2	1.5	12.986
42070966W	8	2	2	13.661
42070963W	8	2	2.5	14.336
42070972W	8	2	3	15.011
42070969W	8	2	3.5	15.686
42070974W	8	2	4	16.361
42070978W	8	2	5	17.711
42070982W	8	2	6	19.061
42070811W	10	3.15	0.5	20.615
42070818W	10	3.15	1	21.69
42070815W	10	3.15	1.5	22.765
42070824W	10	3.15	2	23.84
42070821W	10	3.15	2.5	24.915
42070831W	10	3.15	3	25.99
42070827W	10	3.15	3.5	27.065
42070835W	10	3.15	4	28.14
42070838W	10	3.15	5	30.29
42070842W	10	3.15	6	32.44
42070846W	13	5.3	0.5	19.16
42070853W	13	5.3	1	20.91
42070850W	13	5.3	1.5	22.66
42070860W	13	5.3	2	24.41

42070857W	13	5.3	2.5	26.16
42070868W	13	5.3	3	27.91
42070864W	13	5.3	3.5	29.66
42070871W	13	5.3	4	31.41
42070875W	13	5.3	5	34.91
42070879W	13	5.3	6	38.41
42070891W	16	8	1	32.43
42070887W	16	8	1.5	35.18
42070899W	16	8	2	37.93
42070895W	16	8	2.5	40.68
42070907W	16	8	3	43.43
42070903W	16	8	3.5	46.18
42070911W	16	8	4	48.93
42070915W	16	8	5	54.43
42070919W	16	8	6	59.93

Blueprint

