# Chain Sling G80 3-leg with Foundry Hooks

**Product information**



High quality 3-leg chain sling equipped with foundry hooks. Manufactured with high quality grade 80 components. Chain slings are one of the most popular tools for lifting loads in various industries. They are ideal as auxiliary equipment for transporting and lifting loads. All our slings meet the requirements of EU standards and have CE marking. The main advantages of our lifting slings are high resistance to mechanical damage and temperature, they are 100% safe and offer high WLL with low own weight.

... *Read more*

**Material:** Steel
**Marking:** According to standard, CE-mark
**Temperature range:** -40°C up to +200°C / 400°C = WLL 75%
**Finish:** Painted, black / yellow
**Standard:** EN 818-4

**Safety factor:** 4:1
**Grade:** 8

© November 2026 - All Rights Reserved

Forankra
Secures everything in transit™

# Chain Sling G80 3-leg with Foundry Hooks

## Blueprint




## Technical data

| Part code | Chain diameter mm | WLL ton | EWL m | Weight kg |
|---|---|---|---|---|
| 42071253W | 6 | 2.36 | 0.5 | 16.29 |
| 42071260W | 6 | 2.36 | 1 | 17.49 |
| 42071257W | 6 | 2.36 | 1.5 | 18.69 |
| 42071267W | 6 | 2.36 | 2 | 19.89 |
| 42071263W | 6 | 2.36 | 2.5 | 21.09 |
| 42071275W | 6 | 2.36 | 3 | 22.29 |
| 42071271W | 6 | 2.36 | 3.5 | 23.49 |
| 42071278W | 6 | 2.36 | 4 | 24.69 |
| 42071282W | 6 | 2.36 | 5 | 27.09 |
| 42071286W | 6 | 2.36 | 6 | 29.49 |
| 42071290W | 8 | 4.25 | 0.5 | 20.283 |
| 42071297W | 8 | 4.25 | 1 | 22.308 |
| 42071294W | 8 | 4.25 | 1.5 | 24.333 |
| 42071304W | 8 | 4.25 | 2 | 26.358 |
| 42071301W | 8 | 4.25 | 2.5 | 28.383 |
| 42071312W | 8 | 4.25 | 3 | 30.408 |
| 42071308W | 8 | 4.25 | 3.5 | 32.433 |
| 42071315W | 8 | 4.25 | 4 | 34.458 |
| 42071319W | 8 | 4.25 | 5 | 38.508 |
| 42071323W | 8 | 4.25 | 6 | 42.558 |
| 42071145W | 10 | 6.7 | 1 | 27.52 |
| 42071137W | 10 | 6.7 | 0.5 | 29.395 |

© November 2026 - All Rights Reserved

Forankra
Secures everything in transit™

# Chain Sling G80 3-leg with Foundry Hooks

## Technical data

| Part code | Chain diameter mm | WLL ton | EWL m | Weight kg |
|---|---|---|---|---|
| 42071141W | 10 | 6.7 | 1.5 | 30.745 |
| 42071152W | 10 | 6.7 | 2 | 31.42 |
| 42071149W | 10 | 6.7 | 2.5 | 37.195 |
| 42071159W | 10 | 6.7 | 3 | 37.87 |
| 42071155W | 10 | 6.7 | 3.5 | 43.645 |
| 42071162W | 10 | 6.7 | 4 | 49.42 |
| 42071166W | 10 | 6.7 | 5 | 50.77 |
| 42071170W | 10 | 6.7 | 6 | 57.22 |
| 42071174W | 13 | 11.2 | 0.5 | 36.06 |
| 42071182W | 13 | 11.2 | 1 | 41.31 |
| 42071178W | 13 | 11.2 | 1.5 | 46.56 |
| 42071190W | 13 | 11.2 | 2 | 51.81 |
| 42071186W | 13 | 11.2 | 2.5 | 57.06 |
| 42071198W | 13 | 11.2 | 3 | 62.31 |
| 42071194W | 13 | 11.2 | 3.5 | 67.56 |
| 42071201W | 13 | 11.2 | 4 | 72.81 |
| 42071205W | 13 | 11.2 | 5 | 83.31 |
| 42071209W | 13 | 11.2 | 6 | 93.81 |
| 42071221W | 16 | 17 | 1 | 55.49 |
| 42071217W | 16 | 17 | 1.5 | 63.74 |
| 42071229W | 16 | 17 | 2 | 71.99 |
| 42071225W | 16 | 17 | 2.5 | 80.24 |
| 42071237W | 16 | 17 | 3 | 88.49 |
| 42071233W | 16 | 17 | 3.5 | 96.74 |
| 42071241W | 16 | 17 | 4 | 104.99 |
| 42071245W | 16 | 17 | 5 | 121.49 |
| 42071249W | 16 | 17 | 6 | 137.99 |

© November 2026 - All Rights Reserved